


BOLON FLOORING

BOLON BY PATRICIA URQUIOLA

TECHNICAL SPECIFICATION

Woven vinyl flooring, product standard EN 1307.

INCLUDED IN EN 1307		ROLLS	
	Use classification	ISO 10874	33 Heavy Commercial
	Weight	ISO 8543	3,1 kg/m ²
	Thickness	ISO 1765	2,4 mm
	Roll dimension	EN 426	2000 mm, 25 m
	Tile dimension	EN 994	-
	Castor Chair	EN 985	Intensive use
	Body Voltage	EN 1815**	Fulfilled
	Thermal resistance	ISO 8302	Suitable for underfloor heating
	Impact sound insulation*	EN ISO 10140	9 dB
	Airborne sound absorption*	EN ISO 354 α_w	0,05
	Airborne sound absorption*	EN ISO 354 α_s	250 Hz 0,01 500 Hz 0,01 1000 Hz 0,05 2000 Hz 0,09
	Colour fastness to light*	EN ISO 105-B02	> 7
	Dimension stability	ISO 2551 EN 986	Fulfilled
ADDITIONAL TESTS			
	Anti slip property	DIN 51130	R9
	Friction	EN 13893	> 0,3
	Pendulum	EN 13036-4	88-93
	Reaction to fire	EN 13501-1	B _{fl} -s1
	Critical radiant flux	ASTM E 648	Class 1
	Smoke density	ASTM E 662	< 450

* Typical value

** EN 1815 replaces ISO 6356

BOLON FLOORING

BOLON BY PATRICIA URQUIOLA

CERTIFICATES AND SUSTAINABILITY

For complete information and market specific certificate, visit bolon.com or contact customer service.

SUSTAINABILITY		ROLLS
Recycled content	ISO 14021	18% Pre-consumer material
Carbon footprint CO2e/m ²	EN 15804 (A1-A3)	5,74
CERTIFICATES		
CE		419005
Emissions		M1, Floorscore, VOC A+
Raw material		Best Practice PVC
LCA		EPD, GreenTag
Content/chemicals		GreenTagPHD, Follows req. of BASTA
REGISTERED/LISTED		
BASTA		Yes
BRE Global Listed		Yes
Byggarbedömningen		Yes
DGNB navigator		Yes
eBVD		Yes
ECOproduct		Yes
GBR kretsloppsmärkning		Yes
SundaHus		Yes



BYGGMATERIALS
2021 Global services



THE NORWEGIAN
ASTHMA AND ALLERGY
ASSOCIATION
- making people healthier

BOLON

Bolon HQ: Industrivägen 12, 523 90 Ulricehamn, Sweden
bolon.com | info@bolon.com | [@bolonofficial](https://twitter.com/bolonofficial)

September, 2021